SR Smith. deck profile sheet POOL lift* PAI PAL2 Splash! Splash! 300 aXs multiLift 1. Preferred Lift: ML300 2. Gutter Configuration: Fully recessed Fully recessed gutter Partially recessed **Bull Nose Coping** w/parapet gutter gutter В Florida Rollout w/curb Rollout gutter Standard Flush gutter and deck w/ or w/o bullnose backyard pool D If none of the images above match your gutter configuration, please draw the shape on a separate piece of paper and attach. 3. Deck Material (check one): Concrete Pavers **POOL 4.** Distance from pool deck to water line (A): Check this box to confirm that 5. Height of curb (B): you have checked to make sure the location of the lift will 6. Width of curb (C): meet the ADA Clear Deck 7. Width of gutter (D): Space Requirement (1009.2.3): "On the side of the seat opposite the water, a 8. Bull Nose Radius (E): clear deck space shall be provided parallel with 9. Decorative stone setback: the seat. The space shall be 36" wide minimum and shall extend forward 48" minimum from a 10. Is your pool located on the ground level? Yes line located 12" behind the rear edge of the Note: Pool lifts are application specific. Please provide accurate measurements for your pool in the space provided. S.R.Smith will confirm that the lift selected will meet the location and installation requirements based on the ADA Design Standards (2010) or suggest an alternative lift that will meet the requirements. S.R.Smith bears no responsibility due to misapplication of a lift without a completed Deck Profile Sheet on record. Fax this completed form to 503.266.4334, email to lifts@srsmith.com,

Name of Distributor Lift Will Be Purchased From	City	State	
Your Name	Email	Phone	
Property or Project Name	PO Number		

S.R.Smith Use Only							
APPROVAL#	O	PAL	O PAL	HI/LO	O PAL SPA	\bigcirc 1	PAL2
O SPLASH	O SPLASH HI/LO	\circ	SPLASH E	ΞR	O SPLASH ER HI/LO		O SPLASH SPA
O SPLASH 300	O SPLASH W/ROU	JND PC	OST O	AXS	O MULTILIFT		ML300

SF-720-003 10/2013